



DUO - core

Corespun Polyester / Cotton (Glace)

Duo-Core is manufactured by Triveni Textiles from the highest quality of 100% cotton staple fibre spun around a high tenacity polyester filament core. This yarn is then further twisted into plies to form a core spun sewing thread.



Duo Core is then glace polished to bind together the fibrous surface of the thread and adds a lustrous finish to the dull appearance of the natural cotton fibre. It is then treated with our own blend of sewing thread lubricant which imparts excellent control of friction during sewing, thus resulting in good loop formation, consistent stitch even on most difficult fabrics or leather.

Duo Core is produced on the most modern machinery using standardised processes at all stages. Raw materials are selected carefully to ensure outstanding quality and guarantees consistent high standards in quality.



Duo Core like all threads from Triveni Textiles is manufactured in accordance with an overriding ecological principal, meets all requirements of the Oeka Tex standards 100. Duo Core is available in more than 220 colours and many more shades as per customer's requirement.

AZO FREE



An ISO 9001 : 2008
Certified Company

Complete thread solution for centuries to come



DUO-core

Corespun Polyester / Cotton (Glace)

PRODUCT DATA

TICKET NO.	PLY	LENGTH	AVERAGE STRENGTH	ELONGATION (%)	COLOUR	TYPE	SUPPLIED IN BOX OF
75	2	5000, 2000 & 1000 mtrs.	2,000g	20-22	White	Vicone	10
50	3	5000, 2000 & 1000 mtrs.	2,900g	20-24	Blue	Vicone	10
36	2	3000, 1500 & 1000 mtrs.	4,100g	22-24	Green	Vicone	10
25	3	3000, 2000 & 1000 mtrs.	5,500g	22-24	White	Vicone	10
20	4	1500, 1000 & 700 mtrs.	8,000g	22-24	Green	Vicone	10
12	2	1000 & 500 mtrs.	11,200g	22-26	Green	Vicone	10
08	3	1000 & 500, mtrs.	15,000g	24-28	Green	Vicone	10
08	3	500 & 300 mtrs.	23,000g	24-28	White	Vicone	10

FASTNESS PROPERTIES

Colour fastness to artificial daylight (ISO 105 B02)	> 5 - 6
Colour fastness to Perspiration (ISO 105 E04)	> 4.5
Colour fastness to Washing 95 C (ISO 105)	> 3
Colour fastness to Water (ISO 105 E01)	> 3 - 4
Colour fastness to Rubbing (ISO 105 X02)	> 3 - 4
Colour fastness to Organic solvent (ISO 105)	> 4



TRIVENI TEXTILES

All facts and figures are intended exclusively for customer information. Above specifications liable to change without any prior notice.

sales@trivenithreads.com

www.trivenithreads.com



An ISO 9001 : 2008
Certified Company