

Heifer is manufactured by Triveni Textiles from the highest quality pre-stabilised, continuous filament Nylon 6.6. Heifer is an excellent sewing thread for all types of natural leather and synthetic hides.

Heifer is treated with our own blend of sewing thread lubricant which imparts excellent control of friction during sewing, thus resulting in good loop formation, consistent stitch even on most difficult fabrics or leather.

Heifer is produced on the most modern machinery using standardised processes at all stages. Raw materials are selected carefully to ensure outstanding quality and guarantees consistent high standards in quality.

**Heifer** like all threads from Triveni Textiles is manufactured in accordance with an overriding ecological principal, meets all requirements of the Oeko Tex standards 100. Heifer is available in more than 470 colours and many more



An ISO 9001 : 2008  
Certified Company

*Complete thread solution for centuries to come*

# HEIFER<sup>®</sup>

Continuous Filament - Nylon 6.6 Sewing Thread



## PRODUCT DATA

| TICKET NO. | TEX | CONSTRUCTION DENIER * PLY | LENGTH                  | AVERAGE STRENGTH | ELONGATION (%) | THREAD CARRIER | RECOMM. NEEDLE SIZE |
|------------|-----|---------------------------|-------------------------|------------------|----------------|----------------|---------------------|
| 80         | 35  | 110*3                     | 5000, 2000 & 1000 mtrs. | 2,300g           | 16 - 26        | Kingspool      | Nm 80-100           |
| 60         | 45  | 210*2, 140*3              | 5000, 2000 & 1000 mtrs. | 3,100g           | 16 - 28        | Kingspool      | Nm 80-110           |
| 40         | 70  | 210*3                     | 3000, 1500 & 1000 mtrs. | 5,100g           | 16 - 28        | Kingspool      | Nm 90-120           |
| 30         | 90  | 210*4, 280*3              | 3000, 2000 & 1000 mtrs. | 6,500g           | 17 - 30        | Kingspool      | Nm 110-130          |
| 20         | 135 | 420*3                     | 1500, 1000 & 700 mtrs.  | 9,400g           | 17 - 30        | Kingspool      | Nm 120-140          |
| 15         | 180 | 630*3                     | 1000 & 500 mtrs.        | 14,600g          | 17 - 30        | Kingspool      | Nm 130-160          |
| 10         | 270 | 840*3                     | 1000 & 500, mtrs.       | 19,400g          | 17 - 32        | Kingspool      | Nm 160-200          |
| 08         | 350 | 1050*3                    | 500 & 300 mtrs.         | 27,000g          | 17 - 32        | Kingspool      | Nm 180-230          |

## FASTNESS PROPERTIES

|   |         |
|---|---------|
| Colour fastness to artificial daylight ( ISO 105 B02) | > 5 - 6 |
| Colour fastness to Perspiration ( ISO 105 E04)        | > 4.5   |
| Colour fastness to Washing 95 C ( ISO 105 C04)        | > 3     |
| Colour fastness to Water ( ISO 105 E01)               | > 3 - 4 |
| Colour fastness to Rubbing ( ISO 105 X02)             | > 3 - 4 |
| Colour fastness to Organic solvent ( ISO 105 X05)     | > 4     |



Also available in Anti Wick, Bonded & Anti Static finish.

## TRIVENI TEXTILES

All facts and figures are intended exclusively for customer information. Above specifications liable to change without any prior notice.

sales@trivenithreads.com

www.trivenithreads.com



An ISO 9001 : 2008  
Certified Company